



BLACK ELECTROPHORETIC STEEL PIPE

RIGID STRUCTURE

BASIC INFO

Number of Connections:

None

Number of Set Screws:

None

Finishes Available:

Black

Piece Allow Movement:

No

Black Electrophoretic Steel Pipe is meant to only be used for SteelTek fittings. Not meant to sit in water for long periods of time. The minimum wall thickness at any point shall be not more than 12.5 % under the nominal wall thickness specified. Pipe ordered under structural pipe is intended for mechanical applications and is also acceptable for ordinary structural uses.

FEATURES:

- Black electrophoretic coating for corrosion resistance
- Iron construction for durable performance
- Easy installation and removal, no permanent connections
- No special tools needed
- Use an Allen Wrench for connections
- Able to operate in temperatures ranging from -20°C to 300°C

Part #	Nominal Pipe Size	Pipe Length	Pipe OD (in)	Weight (lbs)
582-040PE30HC	3/8in	4in	0.68	0.56
582-060PE30HC	3/8in	6in	0.68	0.56
582-120PE30HC	3/8in	12in	0.68	0.56
582-180PE30HC	3/8in	18in	0.68	0.56
582-240PE30HC	3/8in	24in	0.68	0.56
582-360PE30HC	3/8in	36in	0.68	0.56
584-040PE30HC	3/4in	4in	1.050	0.93
584-060PE30HC	3/4in	6in	1.050	0.93
584-120PE30HC	3/4in	12in	1.050	0.93
584-180PE30HC	3/4in	18in	1.050	0.93
584-240PE30HC	3/4in	24in	1.050	0.93
584-360PE30HC	3/4in	36in	1.050	0.93